



Castrol Activ 2T

Piston Guard formula

Description

Castrol Activ 2T is a modern, high quality 2-stroke engine oil. Its Piston Guard formula is designed to provide continuous protection against the buildup of carbon deposits on the engine and spark plug during use, keeping them clean to ensure fast and reliable starting

Application

Castrol Activ 2T is suitable for use in all 2-stroke motorcycle and scooter engines from both European and Japanese manufacturers. It is designed for both oil injection and pre-mix lubrication, as per manufacturers' instructions, up to a fuel/oil ratio of 50:1

Advantages

- Continuous Protection
- Protect components from deposits in use
- Good lubricity, protecting pistons from scuffing
- Good protection against exhaust system blocking
- Low ash formulation to reduce pre-ignition & catalyst deterioration
- Designed for both oil injection and pre-mix systems up to 50:1

Typical Characteristics

Name	Method	Units	Typical
Density @ 15C, Relative	ASTM D4052	g/ml	0.86
Viscosity, Kinematic @ 100°C	ASTM D445	mm ² /s	7.5
Pour Point	ASTM D97	°C	-36
Total Base Number, TBN	ASTM D2896	mg KOH/g	1.9
Viscosity, Kinematic @ 40°C	ASTM D445	mm ² /s	42.5
Flash Point, PMCC	ASTM D93	°C	86
Ash, Sulphated	IP 163	% wt	0.09

Product Performance Claims

ISO-L-EGD
JASO FD

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Activ 2T
07 Sep 2018
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 132 McCredie Road, Guildford NSW 2161, Australia
Technical Advice Line 1300 557 998 Customer Service 1300 554 890
www.castrol.com.au www.msds.castrol.com.au