

Toyota Hilux / Fortuner 2015-on 2.4L / 2.8L Turbo Diesel Gun126R 1GD-FTV EGR

OS-PROV-12



INLET →

← **OUTLET**

WARNING: Engine damage will occur if incorrectly connected. Please follow Installation Guide

For vehicles that have travelled over 80,000 kms we recommend an intake manifold clean !

MANN Provent 200 IV Oil Catch Can Kit Install Guide

CAUTION: ** Ensure the engine is OFF & COOL before installation ! **

STEP 1: Identify Install Area. Driver's side of engine bay.

STEP 2: Loosen the existing Fittings to Fit the Kit Bracket. Position the Kit Bracket, return the Fittings and then secure.

STEP 3: Unlatch the Provent plastic body bracket and swivel ports in to position. Fit the Drain Hose to the base of the Provent unit and clamp.

STEP 4: Feed the Drain Hose down through the chasis between the rubber inner guard and the outside of the chassis rail. Secure with supplied P-Clamp.

**** Ensure the Drain TAP is CLOSED ! ****



STEP 1:



STEP 2:



STEP 3:



STEP 4:

Toyota Hilux / Fortuner 2015-on 2.4L / 2.8L Turbo Diesel Gun126R 1GD-FTV EGR

OS-PROV-12

STEP 5: Fit Provent on to Vehicle Specific Kit Bracket.**STEP 6:** Release the Factory Air Intake Hose from Top of Crankcase and Re-route towards Provent.**STEP 7:** Connect the supplied Short Hose to Provent Lower Outlet, connect the Air Intake Hose. Tighten all hose clamps.**STEP 8:** Connect the supplied Longer Hose to the Provent Top Inlet. Bend around and fit to the Crankcase Outlet. Tighten hose clamps.**STEP 9:** Re-install the engine cover and the job is done !View Install Slide Presentation: [SCAN QR-CODE \(page.1\) >](#)**STEP 5:****STEP 6:****STEP 7:****STEP 8a:****STEP 8b:****STEP 9:**