

Toyota Hiace 2.8L Turbo Diesel 2019-on GDH322R 1GD-FTV

OS-PROV-40

**WARNING: Engine damage will occur if incorrectly connected. Please follow Installation Guide**  
For vehicles that have travelled over 80,000 kms we recommend an intake manifold clean !

**MANN Provent 200 IV Oil Catch Can Kit Install Guide**

**CAUTION: \*\* Ensure the engine is OFF & COOL before installation ! \*\***

- STEP 1:** Identify Install Area (driver side). Remove engine cover.
- STEP 2:** Identify & Remove Air Box
- STEP 3:** Adjust Provent Inlets in to displayed position.  
Fit Drain Hose to the base of the Provent Unit.  
Tighten the hose clamp.
- STEP 4:** Fit the Bracket using the OEM factory Fittings.



**STEP 1:**



**STEP 2:**



**STEP 3:**



**STEP 4:**

Toyota Hiace 2.8L Turbo Diesel 2019-on GDH322R 1GD-FTV

OS-PROV-40

**STEP 5:** Connect the supplied Long Hose to Provent's Top Inlet - Secure with supplied clamps.

**STEP 6:** Connect the supplied Short Hose to Provent's Lower Outlet - Secure with supplied clamps.

**STEP 7:** Fit the Provent to the Bracket using the supplied fittings.  
Feed the clear Drain Hose down through the engine bay.  
Cut the Drain Hose the desired length and fit the Drain Tap - Tighten hose clamp.

\*\*\* Ensure Drain Tap is CLOSED \*\*\*

**STEP 8:** Disconnect the Factory Hose that runs from the top Crankcase Outlet (CCO).

**STEP 9:** Connect the Hose from Provent's Top Inlet to the Crankcase Outlet - Secure with supplied clamps.  
Connect the Hose from Provent's Lower Outlet to the Air Intake Breather Hose - Secure with supplied clamps.

**STEP 10:** Cable-tie hoses to prevent rubbing. Re-fit engine cover. Your done !

View the Install Slide Presentation: [SCAN QR-CODE on page 1 >](#)



STEP 5:



STEP 6:



STEP 7:



STEP 8:



STEP 9:



STEP 10: